



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[60760-00087-01](#)

[60760-00088-01](#)

[60760-00094-01](#)

[60760-00095-01](#)

[60760-00096-01](#)

[60760-00098-01](#)

[60760-00001-01](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant

tesaflex® 60760 PV1

Floor Marking Tape

PRODUCT INFORMATION

Product Description

tesaflex® 60760 is a tough plasticized PVC tape coated with an aggressive modified rubber-resin adhesive, which allows adhesion on many different surfaces. tesaflex® 60760 is even tearable by hand.

Main Application

tesaflex® 60760 is perfectly suitable for temporary and low duty hazard warning & marking of any kind of mobile or static objects.

Technical Data

■ Backing material	soft PVC	■ Adhesion to steel	2.5 N/cm
■ Total thickness	150 µm	■ Elongation at break	160 %
■ Type of adhesive	natural rubber	■ Tensile strength	28.02 N/cm

Properties

- Suitable for rough surfaces ++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesaflex® 60760 is also available with two highly visible colour-modes which accord to safety-regulations.

For latest information on this product please visit <http://l.tesa.com/?ip=60760>

Page 1 of 1 / As of 12/01/13

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101
<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle,
Singapore 629621
Phone: +65 (68) 612 026
Fax: +65 (68) 614 790
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[60760-00087-01](#)

[60760-00088-01](#)

[60760-00094-01](#)

[60760-00095-01](#)

[60760-00096-01](#)

[60760-00098-01](#)

[60760-00001-01](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant